

TOSHIBA

e-STUDIO™ 2525AC/3025AC/3525AC/4525AC

- High-Speed – Up to 25, 30, 35 & 45PPM
- Compact Design
- Advanced Security Features
- Solutions Ready
- Environmentally Friendly



e-STUDIO™ 2525AC/3025AC/3525AC/4525AC

MAIN SPECIFICATIONS

| | |
|---------------------------------|--|
| Copy System | Indirect Electrostatic Photographic/OPC/Laser Printing/Heat Roller Fusing |
| Display | 10.1" Color WSVGA Touch Screen Tilting Display |
| Copy Speed | 25/30/35/45 PPM (LT) |
| First Copy Out | Color: Less Than 7.8/7.8/7.8/5.7 Seconds Monochrome: Less Than 5.9/5.9/5.9/4.4 Seconds |
| Warm-Up Time | From powering on: Approx. 20 Seconds From Sleep & Low Power: Less Than 12 Seconds |
| Copy Resolution | 600 x 600 dpi |
| Stack Feed Bypass | 3.9" x 5.8" to 12" x 18", 12" x 47" Banner, Envelope |
| Multiple Copying | Up to 999 Copies |
| Paper Capacity | Standard 1,200 Sheets/Max. 5,200 Sheets |
| Original Feed | 300-Sheet DSD/ or DSD/ with Double Feed Detection or 100-Sheet RADF |
| Scan Speed & Weights | DSD/ Scan: 70IPM (Monochrome or Color), Simplex or Duplex: 9.3-110lb Bond RADF Scan: 50IPM (Monochrome or Color), Simplex: 9.3-41.8lb Bond, Duplex: 13.3-41.8lb Bond |
| Max. Original Size | LD/A3 |
| Paper Feed Sizes | Drawer 1: 550 Sheets-ST-R to LD Drawer 2: 550 Sheets-ST-R to 12" x 18" Stack Feed Bypass: 100 Sheets-3.9" x 5.8" to 12" x 18", 12" x 47" Banner Opt. 550-Sheet Paper Feed Pedestal-ST-R to 12" x 18" Opt. 550-Sheet Drawer for PFP-ST-R to 12" x 18" Opt. Envelope Cassette for PFP-Approx. 60 Envelopes/550 Sheets-ST-R to LG Opt. 2,000-Sheet Tandem LCF (Pedestal Type)-LT Only Opt. 2,000-Sheet External LCF-LT Only Standard: 550 Sheets x 2-16lb Bond-110lb Cover Stack Feed Bypass: 100 Sheets-14lb Bond-110lb Cover Opt. 550-Sheet Paper Feed Pedestal-16lb Bond-110lb Cover Opt. 550 Sheets Drawer for PFP-16lb Bond-110lb Cover Opt. Envelope Cassette for PFP-16lb Bond-140lb Index Opt. 2,000-Sheet Tandem LCF (Pedestal Type)-17lb-28lb Bond Opt. 2,000-Sheet External LCF-LT 16lb Bond-110lb Cover Standard Automatic Duplex Unit (16lb Bond-140lb Index) |
| Paper Weights | 25% to 400% Max. 75K/90K/105K/105K Month (Color: 100%) Max. 150K/180K/210K/210K Month (Monochrome: 100%) Approx. 169lb/172lb 23" (W) x 25.2" (D) x 31" (H) CMY: 38K, K: 39.8K @ 5% 120 Volts, 50/60 Hz, 12 Amps Maximum 1.8kW (120V) NEMA 5-15 4GB 128GB Solid State Drive (SSD) |
| Duplex | |
| Reproduction Ratio | |
| Max Duty Cycle | |
| Weight | |
| Approx. Dimensions | |
| CMYK Toner Yield | |
| Power Source | |
| Power Consumption | |
| Plug Type | |
| Memory | |
| Hard Disk Drive | |

e-BRIDGE NEXT PRINT SPECIFICATIONS

| | |
|-------------------------------|---|
| PDL | PCL5e, PCL5c, PCL6 (PCL XL), PS3, PDF, XPS, JPEG |
| Print Resolution | 600 x 600 dpi (5 bit), 1,200 x 1,200 dpi (Color/2 bit) or 3,600 (Equivalence) x 1,200 dpi (BW/with Smoothing) (PS3 Only) |
| Operating Systems | Windows® 8.1, 10, 11, Windows Server® 2012/R2, Windows Server® 2016/19/22, Macintosh® (macOS X 10.10-15, 12), Unix®, Linux® TCP/IP (IPv4, IPv6), NetBIOS over TCP/IP, IPX/SPX® for Novell® Environments, EtherTalk for Macintosh Environments |
| Network Protocols | SMB V1-3, LPR/LPD, IPP V1.2 w/Authentication (TLS 1.2/1.3), AppleTalk® PAP or EtherTalk, Port 9100 (Bi-Directional), NetWare P-SERVER LPD |
| Printing Protocols | w/Print, Bluetooth (HCRP/BIP/OPP/FTP), WS Print, FTP |
| Print Drivers | Windows® 8.1 (32-bit, 64-bit), Windows Server® 2012/R2 (64-bit), Windows Server® 2016/19/22, Windows® 10, 11 (64-bit), macOS X 10.12-15, 11, 12 |
| Interface | RJ-45 Ethernet (10/100/1000 Base-T), USB 2.0 (High-Speed) Optional IEEE802.11b/g/n, Wireless LAN, Optional Bluetooth |
| Wireless Device | AirPrint®, Mopria®, e-BRIDGE Print & Capture Application on iOS and Android (Available via Apple® App Store or Google Play) |
| Device Management | TopAccess |
| Account Control | Up to 10,000 Users or 1,000 Departments Supports User Authentication (on Device), Login Name/Password (via Windows® Domain) or Login Name/Password (via LDAP Server) for Copy, Print, Scan, Fax, List, and User Function |
| Accessibility Features | Tilt Front Panel, Job Programs, Universal Grip for Paper Trays, Disable Screen Timeout, Audible Beeps, Optional Voice Assist |



Security Features

User Authentication, Trusted Platform Module, On-Board Data Scramble Function, SCEP, Disable, e-Filing, Disable Copy, Disk Overwrite, IP Address Filtering (10 Sets), MAC Address Filtering (10 Sets), Network Service Control, Network Port Control, SMB Packet Signing, SSL/TLS (HTTP, IPP, LDAP, SMTP, POP, FTP, DPWS, SYSLOG), IPsec (IKEv1, IKEv2), Security Mode Change, CC Certified (ISO/IEC15408)* with HCD-PP v1.0, IEEE802.1X (Wired/Wireless), Digital Signature for Client Utilities, Password Policy, Password Lock, Password Expiration, Self Testing, Job Access Control, Log Access Control for Job Log, Security Stamp, Role Based Access Control, Secure PDF, Digital Signature for Firmware Update, Integrity Check Function, Image Log, Card Authentication, Biometric Authentication *Conformance with HCD-PPv1.0 in High Security Mode ENERGY STAR® (V3.1), EPEAT Gold, Californian Proposition 65 WHQL (Windows® 8, 8.1, 10, 11, 2012, 2012 R2, 2016/19/22), Novell®, Citrix®, SAP, AirPrint® and Mopria®

Environmental Standards Certifications

SCAN SPECIFICATIONS

| | |
|--------------------------|---|
| Scan Speed | DSD/ Scan: Up to 240 IPM Duplex, 120 IPM Simplex (Monochrome or Color) RADF Scan: Up to 73 IPM (Monochrome or Color) |
| Scan Modes | Standard: Full Color, Auto Color, Monochrome, Grayscale |
| OCR | DOC/XLS/PPT/PDF |
| Scan Resolution | 600 dpi, 400 dpi, 300 dpi, 200 dpi, 150 dpi, 100 dpi |
| File Formats | Monochrome: TIFF-Multi/Single Page, PDF-Multi/Single Page, PDF/A, Searchable PDF, XPS-Multi/Single Page, DOCX, XLSX, PPTX, Color/Grayscale: JPEG, TIFFMulti/Single Page, PDF-Multi/Single Page, PDF/A, Slim PDF, Searchable PDF, XPSMulti/Single Page, DOCX, XLSX, PPTX |
| Image Compression | Color/Grayscale: JPEG (High, Middle, Low) |

FACSIMILE SPECIFICATIONS

| | |
|----------------------------|---|
| Compatibility | Super G3 |
| Data Compression | MH/MR/MMR/JBIG |
| Transmission Speed | Approx. 3 Seconds Per Page |
| Fax Modem Speed | Up to 33.6 Kbps |
| Memory Transmission | 100 Jobs (with HDD), 2,000 Destinations Max. 400 Destinations/Job |
| Scan Speed | 0.7 Seconds Per Page, Maximum 73 IPM |

e-FILING SPECIFICATIONS

| | |
|--------------------------|---|
| Operation Method | Color Touch Screen Control Panel or Client PC |
| Number of Boxes | 1 Public Box, 200 Private User Boxes |
| Capacity of Boxes | 100 Folders Per Box, 400 Documents Per Folder/Box, 200 Pages Per Document |

ACCESSORIES (OPTIONS)

| | | | |
|---|------------|--|------------|
| Platen & Document Feeder Options | | IPSec Enabler | GP1080NODE |
| DSD/ | MR4010 | Unicode Font Enabler | GS1007NODE |
| DSD/ with Double Feed Detection | MR4020 | Multi-Station Print Enabler | |
| RADF | MR3033 | Per Seat License | GS1090NODE |
| Platen Cover | KA5005PC | e-BRIDGE Plus for OneDrive for Business V3.0 | GB2300NODE |
| Additional Paper Options | | e-BRIDGE Plus for SharePoint Online V3.0 | GB2310NODE |
| Paper Feed Pedestal | KD1072 | e-BRIDGE Plus for Exchange | |
| Drawer Module | MY1052 | Online V3.0 | GB2320NODE |
| Envelope Cassette Option | MY1053 | e-BRIDGE Plus for Gmail | GB2380NODE |
| Large Capacity Feeder | KD1073LT | e-BRIDGE Plus for Google Workspace | GB2390NODE |
| External Large Capacity Feeder | MP2002 | Hardcopy Security Printing | GP1190NODE |
| Finishing Options | | Security SSD (512GB) | GE1280 |
| 50-Sheet Inner Finisher | MJ1048 | FIPS HDD (320GB) | GE1260 |
| 65-Sheet Staple Finisher | MJ1113 | e-BRIDGE Plus Voice Guidance | GB2540NODE |
| 65-Sheet Saddle-Stitch Finisher | MJ1114 | e-BRIDGE Global Print | GB2550NODE |
| Hole Punch for MJ1048 | MJ6011 | Miscellaneous Options | |
| Hole Punch for MJ1113/MJ1114 | MJ6107 | Card Reader Holder | GR1320 |
| Bridge Kit | KN5005 | Accessory Tray | GR1330 |
| Job Separator | MJ5015 | Panel 10-Key Option | GR1340 |
| Connectivity/Security Options | | Stand | STAND5015 |
| FAX Unit/2 nd Line for FAX Unit | GD1370N | Work Tray | KK5005 |
| Wireless LAN/Bluetooth | GN4030A3 | Manual Pocket | KK5008 |
| Fax Over IP License Key | GS1100NODE | Harness for Coin Controller | GQ1280 |
| Bluetooth Keyboard | GR9001 | Accessible Arm | KK2560 |
| 2 nd NIC Holder | GR1430 | | |
| USB Hub | GR1420 | | |
| Meta Scan Enabler | GS1010NODE | | |

Designs and specifications subject to change without notice. Specifications may vary by conditions of use and/or environmental usage. For best results and reliable performance, always use supplies manufactured or designated by Toshiba. Not all options and accessories may be available at the time of product launch. Please contact a local Authorized Toshiba Dealership for availability. Toner yields are estimates based on 5% coverage, letter-size page. Driver and connectivity feature support varies by client/network operating system. Product names may be trademarks of their respective companies. AirPrint® and the AirPrint® logo are trademarks of Apple Inc. This is a Class 1 laser product complying with IEC60825-1. All company and/or product names are trademarks and/or registered trademarks of their respective manufacturers in their markets and/or countries.

Corporate Office

25530 Commercentre Drive, Lake Forest, CA 92630
Tel: 949-462-6000

East Coast

959 Route 46 East, 5th Floor, Parsippany, NJ 07054
Tel: 973-316-2700

Midwest

8770 W. Bryn Mawr Ave., Suite 700, Chicago, IL 60631
Tel: 773-380-6000

South

2037 Bakers Mill Rd., Dacula, GA 30019
Tel: 678-546-9385

West Coast

25530 Commercentre Drive, Lake Forest, CA 92630
Tel: 949-462-6000

Website

www.business.toshiba.com