

CS MZ4000i: The future is here!

The Copystar MZ4000i is an outstanding A3 black and white MFP that combines Kyocera's unbeatable industry expertise with incredible quality to provide long-term solutions that meet the demand of the modern workplace.



CS MZ4000i

BASIC SPECIFICATIONS

Configuration: BW MFP - Print/Scan/Copy/Optional Fax Speed (print only):

Letter: 40 ppm, Legal: 21 ppm, Ledger: 21 ppm Warm Up Time: 18 seconds or less (power on) First Page Out: Copy: 3.6 seconds / Print: 4.2 seconds Display: 10.1" Color Touch Screen Control Panel

Memory/Hard Disk Drive: Std. 4GB RAM/32GB SSD/ 320GB HDD, 1TB HDD (option)

Duplex: standard stackless duplex supports $5.5" \times 8.5"$ to 11" x 17", 16 lb. Bond - 90 lb. Index (60 - 163gsm)

Standard Output Tray: 5.5" x 8.5" - 11" x 17"/250 sheets **Electrical Requirements:**

120V/60Hz/9.9A; 220-240V, 50/60Hz, 6.3A Typical Electricity Consumption (TEC): 120V: .50 kWh/week; 220V: .53 kWh/week Dimensions: 23.3" W x 27.4" D x 26.8" H Weight: 178.5 lbs

Maximum Monthly Duty Cycle: 165,000 pages per month

PAPER SUPPLY

Paper Capacity: Standard 1,100-sheets; Maximum 4.100-sheets Standard Paper Sources: Dual 500-sheet travs. 100-sheet MPT. Auto Selection/Switching Standard Paper Size: Tray 1 - 5.5" x 8.5" - 11" x 17" Tray 2 - 5.5" x 8.5" - 11" x 17"

OPTIONAL PAPER SOURCES

MPT: 5.5" x 8.5" - 11" x 17"

PF-791 Dual 500-sheet tray option - 5.5" x 8.5" - 11" x 17" **PF-810** Dual 1,500-sheet tray option - 8.5" x 11"

PAPER WEIGHT

Trays: 16 lb. Bond - 90 lb. Index (60 - 163gsm) MPT: 12 lb. Bond - 140 lb. Index (45 - 256gsm) Input Materials: Standard/Optional Trays: Plain, Bond, Recycled, Transparency (OHP), Cardstock, Envelopes

SECURITY SPECIFICATIONS

Local Authentication, Network Authentication, **Encryption Communication** (IPsec, HTTPS, TLS 1.3, LDAPS, SMTP/POP/FTPS over TLS, SNMPv3), TPM chipset (Trusted Platform Module), S/MIME, SCEP (auto certificate issuance/renewal), OCSP/CRL (certificate validation), Secure Boot (firmware authenticity verification), Run Time Integrity Check, HDD and Memory Overwrite (7x) Mode and HDD Data Encryption (256 bit),
Common Criteria (ISO/IEC-15408/EAL2), IEEE 2600.2, FIPS 140-2 for storage, HCD-PP and FIPS 140-2 for communication require the Data Security Kit 10 option which provides enhanced IPsec encrypted communication

PRINT SPECIFICATIONS

Standard Controller: ARM Cortex-A53/1.6GHz PDLs/Emulations: PRESCRIBE, PCL6, KPDL3 (PS3), XPS, OPEN XPS, PDF; Optional (UG 34): IBM ProPrinter, Line Printer, LQ-850 Print Resolution: Up to 1200 x 1200 dpi Fonts: KPDL3, PCL6, Bitmap OS Compatibility: Windows: 10/11/Server 2012/Server 2012 R2/ Server 2016/Server 2019; Mac OS X v10.0 or later; Chrome OS Mobile Printing: Apple AirPrint®, Mopria Print Service®, KYOCERA Mobile Print, KYOCERA MyPanel remote access Interfaces: Standard: 1000 Base-T/100-Base-Tx/10BASE-T (IPv6, IPv4, IPsec), 802.3az ready, High-Speed USB 3.0, 4 USB 2.0 Host Interfaces, 2 eKUIO Expansion Slots, IEEE 802.11b/g/n Wireless LAN (supports up to 98.5 feet); Optional: IEEE 802.11a/b/g/n/ac (IB-37 for 2.4/5GHz), 10/100/1000BaseTX (IB-50 for Dual NIC); IEEE 802.11b/g/n (IB-51 for Wireless LAN Interface (supports up to 328.1 feet)
Network Print and Supported Protocols: HTTPS, FTPS, SNMP v1/v2c/v3, Raw Port (Port 9100) TCP/IP, IPv4, IPv6, DHCP LPR, DNS, WSD Scan/Print Drivers: KX Driver, PCL Uni-Driver, KPDL Uni-Driver, Microsoft Universal Print Driver, Network Fax Driver, TWAIN Driver, WIA Driver, Status Monitor, Common Profile, Output to PDF, Security Watermark KYOCERA Print Center, MAC Driver, Chrome Print Driver, Linux Driver, KX PRESCRIBE Macro Generator,

Windows Inbox Driver, Linux SANE Driver

Utilities: KYOCERA Net Viewer KYOCERA Device Manager, Quick Setup, ID Register, Software Management Service, Upgrade Studio, Web Package Maker, Removal Tool, Wi-Fi Setup Tool, PDF Direct Print, Command Center RX; Kyocera Net

Manager (option)

SCAN SPECIFICATIONS

Scan Type: Color and Black & White Scanner Scan Resolution: 600/400/300/200 dpi, 200 x 100 dpi, 200 x 400 dpi

File Formats: TIFF, JPEG, XPS, OpenXPS, PDF/A-2.0 (MMR/JPG Compression/High Compression PDF); Option: Scan Extension Kit Text Searchable PDF; MS Office File Types
Connectivity: 10 BASE-T/100 BASE-TX/1000 BASE-T

(IPv4, IPv6, IPSec) TCP/IP, Hi-Speed USB supported protocols Scanning Functions: Scan-to-Folder (SMBv3), Scan-to-Email, Scan-to-FTPS over TLS, Scan-to-USB, PDF Digital Signatures, WSD Scan, Linux SANE Scan, TWAIN Scan, Specified Color Removal,

Border Erase, Preview
Original Size: Up to 11" x 17" (Glass)

Drivers: TWAIN/WIA/Linux SANE Driver/WSD Scan

OPTIONAL DOCUMENT PROCESSORS

Acceptable Originals: 5.5" x 8.5" - 11" x 17"

DP-7140: Reverse Auto Document Processor/50-sheets Speed: Simplex: 50 ipm; Duplex: 16 ipm (BW/Color) Weight: Simplex: 13 lb. Bond — 90 lb. Index (35 — 160gsm) Duplex: 16 lb. - 32 lb. Bond (50 - 120gsm)

DP-7150: Reverse Auto Document Processor/140-sheets Speed: Simplex: 80 ipm; Duplex: 48 ipm (BW/Color) Weight: Simplex: 13 lb. Bond — 90 lb. Index (35 — 160gsm) Duplex: 16 lb. - 32 lb. Bond (50 - 120gsm)

DP-7160 (with multi-feed detection):

Dual Scan Document Processor/320-sheets Speed: Simplex: 100 ipm; Duplex: 200 ipm (BW/Color)
Weights: Simplex: 13 lb. Bond — 120 lb. Index (35 — 220gsm) Duplex: 16 lb. - 120 lb. Index (50 - 220gsm)

DP-7170 (with multi-feed and staple detection):

Dual Scan Document Processor/320-sheets Speed: Simplex: 100 ipm; Duplex: 200 ipm (BW/Color) Weights: Simplex: 13 lb. Bond — 120 lb. Index (35 — 220gsm) Duplex: 16 lb. - 120 lb. Index (50 - 220gsm)

COPY SPECIFICATIONS

Copy Resolution: 600 x 600 dpi Image Mode: Text, Photo, Text/Photo, Graphic/Map Continuous Copy: 1 — 9,999

Additional Features: Auto Magnification, Auto Paper Select, Combine Copy, Mirror Image, Rotate Copy, Border Erase, Margin, Page Number, Form Overlay, Blank Page Skip, Specified Color Removal, Proof Copy, Preview, ID Card Copy Job Management: 1,000 User Codes, Job Build, Shortcut Keys,

Magnification/Zoom: Full Size, 4 Reduction, 4 Enlargement Preset Ratios, 25 – 400% in 1% Step Increments Document Box: Custom/Job

OPTIONAL FAX SPECIFICATIONS

Fax Type: Fax System 12 (option) Type/Data Compression: G3 Fax/MMR, MR, MH, JBIG Transmission Speed/Modem Speed: Less than 3 seconds/33.6 Kbps Fax Memory: Standard 170 MB **Driver:** Network Fax Driver Fax Functions: Network Fax, Duplex Transmission and Reception, Encrypted Transmission and Reception Polling Transmission and Reception, Broadcast, Fax Server Integration, Fax Dedicated Paper Feed Tray, Fax Forwarding to email or file

OUTPUT & FINISHING OPTIONS²

OPTIONAL 1,000 SHEET FINISHER DF-71203:

Stack/Staple Capacity: Main Tray: 1,000-sheets/50-sheets Paper Sizes 5.5" x 8.5" – 11" x 17"

Paper Weight: 14 lb. Bond – 140 lb. Index (52 – 256gsm)

Edge Staple Position: Top Left, Bottom Left, Center Bind Optional Punch PH-7A: 2/3 Hole Punch Unit, supports 8.5" x 11" — 11" x 17"; 14 lb. Bond — 140 lb. Index

Dimensions: 21.6" W x 24.4" D x 41.3" H

OPTIONAL 3.000 SHEET FINISHER DF-7913:

Stack/Staple Capacity: Main Tray (A): 3,000-sheets; Sub Tray (B): 200-sheets; Sub Tray (C):50-sheets/65-sheets Paper Size: $5.5" \times 8.5" - 11" \times 17"$

Paper Weight: 16 lb. Bond — 140 lb. Index (60 — 256gsm)

Edge Staple Position: Top Left, Bottom Left, Center Bind Dimensions: 29" W x 26" D x 42" H

Optional Punch PH-7A: 2/3 Hole Punch Unit,

supports 8.5" x 11" — 11" x 17"; 14 lb. Bond — 140 lb. Index Optional Multi-Bin Mailbox MT-730(B):

(DF-791) 7 Trays; supports: 16 lb. Bond — 90 lb. Index (60 — 163gsm); **Stack Capacity per bin:** 100-sheets: 5.5" x 8.5", 8.5" x 11"; 50-sheets: 8.5" x 14", 11" x 17"

ADDITIONAL OPTIONS

AK-740 Bridge Unit Attachment Kit, HD-16 Large Capacity HDD (1TB), Internet Fax Kit (A), Card Authentication Kit (B), Data Security Kit 10, 2.4GHZ/5GHz Multi-band Wi-Fi option (IB-37), Dual NIC (IB-50), Extended Range Wireless LAN NIC (IB-51), Thin Print option (UG-33), Printer Emulation option (UG-34), DT-730(B) Document Tray, Scan Extension Kit (A) for Text Searchable PDF; Keyboard Holder 10, Numeric Keypad (NK-7130), Cabinet Stand

Only 1 Document Processor can be installed Only 1 Output Option can be installed ³ Requires Bridge Unit Attachment Kit (AK-740)

SOLUTIONS AND SERVICES

Remote Management: Kyocera Fleet Services ready! A highly secure cloud-based monitoring solution that offers real-time visibility into your fleet. Optimize device uptime and be notified when to replenish supplies. Streamline billing with seamless 3rd party application integration, allowing you to focus solely on

Printing Software: Cost Control & Security, Cloud & Mobile,

Content Services: Scanning Applications and Connectors, Intelligent Process Automation, Enterprise Content Management

IT Solutions: Technology Solutions (incl. Data Centers and Cloud), Network Infrastructure, Cybersecurity Solutions Collaboration Solutions

Consulting Services: IT Health Check, CIO as a Service, Healthcare Compliance, Backup and Recovery Planning

Professional Services: Design and Architecture, Project Implementation, Project Management

Managed Services: Help Desk Services, Retainer Services and **Onsite Support**

Document Processing Options



DP-7170

Dual Scan Document Processor 320-sheet capacity w/ multi-feed & staple detect 100 ipm simplex / 200 ipm duplex



DP-7160

Dual Scan Document Processor 320-sheet capacity w/ multi-feed detection 100 ipm simplex / 200 ipm duplex



DF-7150

Reversing Auto **Document Processor** 140-sheet capacity 80 ipm simplex / 48 ipm duplex



DP-7140

Reversing Auto **Document Processor** 50-sheet capacity 50 ipm simplex / 16 ipm duplex

Document Finishing Options



the DF-7120 Finisher Resides in the Finisher

DF-7120

1,000-sheet Finisher Staples up to 50-sheets



AK-740

Attachment Kit required for both the DF-7120 and DF-791 Finishers



DT-730 (B) **Original Holder**

Optional platform that holds originals prior to copying



NK-7130 **Numeric Keypad**

Provides additional hard key option for the User Interface



MT-730 (B)

7-Bin Mailbox Option Installed on top of the DF-791 Finisher Holds 100-sheets/Bin

PH-7A

2/3 Hole Punch Unit for the DF-791 Finisher Resides in the Finisher



DF-791

3,000-sheet Finisher Staples up to 65-sheets



Dual 500-sheet Paper Tray Option 5.5" x 8.5" to 11" x 17"



PF-810

Dual 1,500-sheet Paper Tray Option 8.5" x 11"

IB-37

HD-16

Data Security Kit 10

FAX System 12

Internet FAX Kit (A)

TASKalfa MZ4000i

Additional Paper Feeding Options

Card Authentication Kit (B)

IB-50 Gigabit Ethernet Board for Dual NIC

IB-51 Wireless LAN NIC

PLATEN TYPE E

UG-33 Thin Print

UG-34 Optional Printer Emulation

Scan Extension Kit (A)

Keyboard Holder 10

DT-730 (B) Original Hard Copy Holder



Specifications and design are subject to change without notice. CS PRESCRIBE, Kyocera Net Manager, Kyocera Net Viewer, Kyocera Device Manager, PDF Direct Print, Command Center RX, and KX Driver are trademarks of The Kyocera Companies. Mac OS and AirPrint are trademarks of Apple, Inc. Mopria is a trademark of Mopria Alliance, Inc. Windows is a trademark of Microsoft, Inc. All other trademarks are the property of their respective owners.







KYOCERA Document Solutions America 225 Sand Road, PO Box 40008 Fairfield, New Jersey 07004-0008, USA Tel: 973-808-8444



Copystar Partner

copystar.com