

The sky's the limit

EvolutionNext is our follow up to the Evolution Series. With award-winning reliability, advanced security, and versatile finishing options, our sustainable design will help your business thrive.


TASKalka MZ2501ci

A3 color copy, print, scan, and optional fax in 1 device

Cloud connectivity out of the box

Up to 25 ppm and up to 274 ipm

True 1200 x 1200 dpi with advanced finishing



TASKalfa MZ2501ci

BASIC SPECIFICATIONS

Configuration: Color Multifunctional System
- Print/Copy/Scan/Optional Fax

Speed: Letter: 25 ppm, Legal: 15 ppm, Ledger: 12 ppm,
12" x 18": 12 ppm (print only)

Warm Up Time: 9.7 seconds or less

First Page Out:

Copy: 6.4 seconds or less Black, 8.5 seconds or less Color
Print: 7.0 seconds or less Black, 9.2 seconds or less Color

Display: 10.1" Color Touch Screen Control Panel

Memory/Hard Disk Drive: 4G RAM/ 256GB SSD
Standard, 1TB HDD (option)

Duplex: Standard Stackless Duplex supports Statement
(5.5" x 8.5") to Ledger (12" x 18"), 16 lb. Bond - 142 lb.
Index (60 – 256gsm)

Standard Output Tray: Statement – 12" x 18"/500 Sheets;
up to 12" x 48" Banner (single sheet)

Electrical Requirements: 120V, 60Hz, 12A;
220-240V, 50/60Hz, 7.2A

Typical Electricity Consumption (TEC): 120V: .29 kWh/week;
220V: .30 kWh/week

Dimensions: 23.7" W x 26.1" D x 31.1" H

Weight: 198.4 lbs

Maximum Monthly Duty Cycle: 100,000 Pages per Month

PAPER SUPPLY

Standard Paper Sources: Dual 500 Sheet Trays, 150 Sheet
MPT, Auto Selection/Switching

Optional Paper Sources: Dual 500 Sheet Trays (PF-7140)
Dual 1,500 Sheet Trays (PF-7150) 3,000 Sheet Capacity Tray
(PF-7120)

Paper Capacity: Standard 1,150 Sheets; Maximum 7,150 Sheets

Paper Size:

Tray 1 – 5.5" x 8.5" – 8.5" x 14" (statement to legal); Tray 2 –
5.5" x 8.5" – 12" x 18", Custom Size; PF-7140: 5.5" x 8.5" –
12" x 18" PF-7150/PF-7120: 8.5" x 11" MPT: 5.5" x 8.5" –
12" x 18" (multiple sheets); Up to 12" x 48" Banner (single sheet)

Paper Weight:

Trays/MPT: 14 lb. Bond – 166 lb. Index (52 – 300gsm)

Input Materials:

Standard/Optional Trays: Plain, Bond, Recycled, Preprinted,
Vellum, Color, Pre-Punched, Thick, Thin, High Quality,
Letterhead, Envelope, Custom; MPT: Plain, Bond, Recycled,
Preprinted, Vellum, Color, Pre-Punched, Thick, Thin, High
Quality, Transparency (OHP), Coated, Index Tab, Label,
Letterhead, Envelope, Custom

SECURITY SPECIFICATIONS

Guarded Access: LDAP, IP Filtering, Secure Print
Release, SMTP Authentication, Create Encrypted PDF,
Failed Authentication Lockout, Card Authentication.

Protected Data Storage: SSD/HDD Overwrite, AES 256 Data
Storage Encryption, Trusted Platform Module, IEC-15408,
Common Criteria, IEEE 2600 Certified, HCD-PP Certified.

Secure Communication: TLS v1.3, SMB 3.1.1, HTTPS, ECDSA,
FIPS 140-3 Encryption, S/ MIME, IPSec with HCD-PP, IPPS
Printing (Over TLS), SCEP Certificated Enrollment, OCSP/
CRL Certificates, 802.1X Ethernet Certificates, SHA 2 384.

Advanced Management: 3 Preset Security Level
Configurations, Remote Management of Fleet, SNMP
v3 Monitoring, SIEM/Syslog Monitoring, Secure Boot
Check, Run Time Integrity Checks, Allow List.

PRINT SPECIFICATION

Standard Controller: ARM Cortex-A53/1.6GHz

PDLs/Emulations: PCL6 (PCL XL/PCL 5c); PRESCRIBE,
KPD L3 (PostScript3 compatible) AES Support, PDF, XPS/
OpenXPS, PPML, Microsoft WPP and Universal Print
Print Resolution: Up to 4800 x 1200 dpi
Fonts: 93 Fonts (PCL6), 136 Fonts (KPD L3), 4 Fonts (Calibri),
4 Fonts (Cambria), 1 Font Bitmap font, 79 Outline fonts
OS Compatibility: Windows: 10/11; Server 2016/Server 2019/
Server 2022/Server 2025; Mac OS X v10.0 or later; Chrome OS

Mobile Printing: Apple AirPrint®, Mopria®,
Kyocera Cloud Print and Scan (KCPS), KYOCERA
Mobile Print, & KYOCERA MyPanel

Interfaces: Standard: 1000Base-T/100Base-Tx/10BASE-T
(IPv6, IPv4, IPsec), IEEE 802.3az; Other Standard: USB
2.0 (Hi-Speed USB), USB 3.0 (Super-Speed USB);
Optional: IEEE 802.11a/b/g/n/ac (IB-37 for 2.4/5GHz),
(IB-38 for 2.4GHz), 10/100/1000BaseTX (IB-53 for
Dual NIC); IEEE 802.11b/g/n (IB-51 for Wireless
LAN Interface (supports up to 328.1 feet)
Optional: IEEE 802.11a/b/g/n/ac (IB-37 for 2.4/5GHz
- IB-38 for 2.4GHz), 10/100/1000BaseTX (IB-53
for Dual NIC); IEEE 802.11b/g/n (IB-51 for Wireless
LAN Interface (supports up to 328.1 feet)

Network Print and Supported Protocols: HTTPS, FTPS, SNMP
v1/v2c/v3, Raw Port (Port 9100) TCP/IP, IPv4, IPv6, DHCP LPR,
DNS, WSD Scan/Print.

Drivers: KX Driver, PCL Mini Driver, KPD L Mini Driver, KX
Driver for XPS, Network Fax Driver, TWAIN Driver, WIA Driver,
Status Monitor, Common Profile, Output to PDF, Security
Watermark, Color Optimizer, MAC Driver, Chrome Print Driver,
Linux Driver, KX Driver with Distributed Printing, Windows
Inbox Driver, SANE Driver.

Utilities: KYOCERA Net Viewer, KYOCERA Device Manager,
Quick Setup, KX PRESCRIBE Macro Generator, ID Register,
Software Management Service, Upgrade Studio, Web Package
Builder/Maker, Removal Tool, PDF Direct Print,
Command Center RX; Kyocera Net Manager (option)

SCAN SPECIFICATION

Scan Type: Color and Black & White Scanner

Scan Resolution: 600 dpi, 400 dpi, 300 dpi, 200 dpi,
200 x 100 dpi, 200 x 400 dpi

File Formats: TIFF, JPEG, XPS, OpenXPS,
PDF, Searchable PDF, MS Office File

Connectivity/Supported Protocols: 10 BASE-T/100
BASE-TX/1000 BASE-T (IPv6, IPv4, IPsec) TCP/IP, Hi-Speed
USB 3.0

Scanning Functions: Scan-to-Folder (SMBv3), Scan-to-Email,
Scan-to-FTPS, Scan-to-FTPS over TLS 1.3, Scan-to-USB, WSD
Scan, DSM/SANE Scan, TWAIN Scan, Specified Color Removal,
Border Erase, Preview

Original Size: Document Processor: 5.5" x 8.5" – 11" x 17";
Glass: Up to 11" x 17"

Drivers: TWAIN/WIA/DSM-SANE Driver/WSD Scan

OPTIONAL DOCUMENT PROCESSORS²

Acceptable Originals: 5.5" x 8.5" – 11" x 17"

DP-7140: Reversing Automatic Document Processor/50 Sheets
Speed: Simplex: 50 ipm (BW/Color); Duplex: 16 ipm (BW/Color)
Weight: Simplex: 13 lb. Bond – 90 lb. Index (45 – 160gsm);
Duplex: 16 lb. – 32 lb. Bond (50 – 120gsm)

DP-7150: Reversing Automatic Document Processor/140 Sheets
Speed: Simplex: 80 ipm (BW/Color); Duplex: 48 ipm (BW/
Color) Weight: Simplex: 13 lb. Bond – 90 lb. Index (35 –
160gsm); Duplex: 16 lb. – 32 lb. Bond (50 – 120gsm)

DP-7160: Dual Scan Document Processor/320 Sheets
Speed: Simplex: 100 ipm BW/Color; Duplex: 200 ipm (BW/
Color) Weights: Simplex: 13 lb. Bond – 120 lb. Index (35 –
220gsm); Duplex: 16 lb. – 120 lb. Index (50 – 220gsm)

DP-7170 (with multi-feed and staple detection):

Dual Scan Document Processor/320 Sheets
Speed: Simplex: 100 ipm (BW/Color); Duplex: 200 ipm
(BW/Color) Weights: Simplex: 13 lb. Bond – 120 lb. Index
(35 – 220gsm); Duplex: 16 lb. – 120 lb. Index (50 – 220gsm)

COPY SPECIFICATIONS

Copy Resolution: 600 x 600 dpi

Image Mode: Text, Photo, Text/Photo, Graphic/Map

Continuous Copy: 1 – 9,999

Additional Features: Auto Magnification, Auto Paper Select,
Combine Copy, Mirror Image, Rotate Copy, Border Erase,
Split Copy, Margin Shift, Page Number, Form Overlay, Blank
Page Skip, Specified Color Removal, Proof Copy, Preview,
ID Card Copy, Handwriting Emphasis, Super Resolution

Job Management: 1,000 User Codes, Job Build, Super
Resolution, Shortcut Keys, Repeat Copy

Magnification/Zoom: Full Size, 4 Reduction, 4 Enlargement
Preset Ratios, 25 – 400% in 1% Step Increments

Document Box: Custom Box, Job Box, USB Drive Box, Fax Box
(with optional Fax System)

OPTIONAL FAX SPECIFICATIONS

Fax Type: Fax System (option)

Type/Data Compression: G3 Fax/MMR, MR, MH, JBIG

Transmission Speed/Modem Speed: Less than 3 seconds/
33.6 Kbps

Fax Memory: Standard 170 MB

Driver: Network Fax Driver

Fax Functions: Network Fax, Duplex Transmission and
Reception, Encrypted Transmission and Reception, Polling
Transmission and Reception, Broadcast, Fax Server Integration,
Fax Dedicated Paper Feed Tray, Fax Forwarding to email or
file

SOLUTIONS AND SERVICES

Remote Management

Kyocera Fleet Services ready! A highly secure cloud-based
monitoring solution that offers real-time visibility into your
fleet. Optimize device uptime and be notified when to
replenish supplies. Streamline billing with seamless 3rd party
application integration, allowing you to focus solely on your
business.

Printing Software

Cost Control & Security, Cloud & Mobile, Printer Management

Content Services

Scan & Connect, Intelligent Process Automation, Enterprise
Content Management

IT Solutions

Technology Solutions, Including solutions for Cloud and Data
Centers; Network Infrastructure, Cybersecurity Solutions,
Collaboration Solutions

Consulting Services

Including IT Health Check, CIO as a Service, Healthcare
Compliance, Backup and Recovery Planning

Professional Services

Including Design and Architecture, Project Implementation,
Project Management

Managed Services

Including Help Desk Services, Retainer Services and On-site
Support

Cloud Ready Services:

Kyocera Cloud Capture (KCC), Kyocera Cloud Information
Manager (KCIM), Kyocera Cloud Print and Scan (KCPS)

Output & Finishing Options³

OPTIONAL 250 SHEET INNER SHIFT TRAY JS-7110

Stack Capacity: 250 Sheets

Paper Size: 8.5" x 11" — 11" x 17"

Paper Weight: 14 lb. Bond — 166 lb. Index (52 — 300gsm)

OPTIONAL 500 SHEET INTERNAL FINISHER DF-7100

Stack/Staple Capacity: 500 Sheets/50 Sheets

Paper Size: 5.5" x 8.5" — 12" x 18"

Paper Weight: 14 lb. Bond — 166 lb. Index (52 — 300gsm)

Edge Staple Position: 3 Positions: Front 1 Staple, Edge 1 Staple, Face 2 Staples

Optional Punch: PH-7100 2/3 Hole Punch Unit, Supports 5.5" x 8.5" — 12" x 18"; 14 lb. Bond — 166 lb. Index (52 — 300gsm)

Dimensions: 19.4" W x 21" D x 6.9" H

OPTIONAL 1,000 SHEET FINISHER DF-7120₄

Stack/Staple Capacity: Main Tray: 1,000 Sheets/50 Sheets (up to 24 lb. Bond [90gsm])

Paper Size: 5.5" x 8.5" — 12" x 18"

Paper Weight: 14 lb. Bond — 166 lb. Index (52 — 300gsm)

Edge Staple Position: 3 Positions: Top Left, Bottom Left, Center Bind

Optional Punch: PH-7A 2/3 Hole Punch Unit, Supports 5.5" x 8.5" — 12" x 18"; 14 lb. Bond — 166 lb. Index (52 — 300gsm)

Dimensions: 21.6" W x 24.4" D x 41.3" H

OPTIONAL 4,000 SHEET FINISHER DF-7140₄

Stack/Staple Capacity: Main Tray (A): 4,000 Sheets; Sub Tray (B): 200 Sheets/65 Sheets (up to 24 lb. Bond [90gsm])

Paper Size: 5.5" x 8.5" — 12" x 18"

Paper Weight: 14 lb. Bond — 166 lb. Index (52 — 300gsm)

Edge Staple Position: 3 Positions: Top Left, Bottom Left, Center Bind

Optional Punch: PH-7A 2/3 Hole Punch Unit, Supports 5.5" x 8.5" — 12" x 18"; 14 lb. Bond — 166 lb. Index (52 — 300gsm)

Dimensions: 29" W x 26" D x 42" H

Optional Booklet Folder/Tri-fold Unit BF-730: (DF-7140)

Booklet Folder supports 8.5" x 11", 8.5" x 14", 11" x 17"; Fold Booklet Staple: 16 lb. — 24 lb. Bond (60 — 90gsm) 20 sheets; 25 lb. — 28 lb. Bond (91 — 105gsm) 13 sheets; Higher than 28 lb. Bond (Higher than 105 gsm) 1 sheet; Fold booklet no staple: 16 lb. — 24 lb. Bond (60 — 90gsm) 5 sheets; 25 lb. Bond — 72 lb. Index (91 — 120gsm) 3 sheets; 32 lb. Bond — 110 lb. Cover (121 — 256gsm) 1 sheet; Trifold supports 8.5" x 11" only: 16 lb. — 24 lb. Bond (60 — 90gsm) 5 sheets; 25 lb. Bond — 72 lb. Index (91 — 120gsm) 3 sheets; 16lb. — 28 lb. Bond (60 — 105gsm) 1 sheet

Optional Multi-Bin Mailbox MT-730(B): (DF-7140) 7 Trays;

Supports: 16 lb. Bond — 90 lb. Index (60 — 163gsm); Stack Capacity per bin: 100 Sheets: 5.5" x 8.5", 8.5" x 11"; 50 Sheets: 8.5" x 14", 11" x 17"

ADDITIONAL OPTIONS

AK-7110 Bridge Unit Attachment Kit, JS-7100 Job Separator, HD-16 Large Capacity HDD (1TB), Banner Guide 10, Internet Fax Kit (A), Card Authentication Kit (B), Dual NIC (IB-53), Extended Range Wireless LAN NIC (IB-51), Thin Print option (UG-33), Printer Emulation option (UG-34), DT-730(B) Document Tray, Scan Extension Kit (A) for Text Searchable PDF; MS Office File, Keyboard Holder 10, Numeric Keypad (NK-7130), Cabinet Stand

¹ Requires PF-7140

² Only 1 Document Processor can be installed

³ Only 1 Output Option can be installed

⁴ Requires Bridge Unit Attachment Kit (AK-7110)

Specifications and design are subject to change without notice. For the latest on connectivity visit kyoceradocumentsolutions.us. TASKalfa, PRESCRIBE, Kyocera Net Manager, Kyocera Net Viewer, Kyocera Device Manager, PDF Direct Print, Command Center RX, and KX Driver are trademarks of The Kyocera Companies. Mac OS and AirPrint are trademarks of Apple, Inc. Windows is a trademark of Microsoft, Inc. All other trademarks are the property of their respective owners.



Kyocera Document Solutions Partner

KYOCERA Document Solutions America
225 Sand Road, PO Box 40008
Fairfield, New Jersey 07004-0008, USA
Tel: 973-808-8444



kyoceradocumentsolutions.us