# **TOSHIBA**

# ©-STUDIO 2822AM/2822AF

- > Black & White Multifunction Printer
- > Up to 28 PPM
- > Small Workgroup
- > Copy, Print, Scan, Fax\*
- > Mobile Enabled

This robust, compact e-STUDIO2822AM/2822AF from Toshiba allows smaller businesses to think even bigger. Copy, print and scan up to ledger-sized output, and add faxing with the AF model. Both models offer high-end functions like an impressive first copy out time of 6.5 seconds and crisp 2,400 x 600 dpi output delivered at 28 pages per minute. For money-savings with two-sided copying and printing, there's a Reversing Automatic Document Feeder (RADF) and Automatic Duplex Unit (ADU). An Ethernet network interface and optional wireless connectivity ensure seamless integration. Mobile users can share the device, thanks to Toshiba's unique e-BRIDGE Print & Capture application.



# ©-STUDIO 2822AM/2822AF

#### **Specifications**

Copying/Printing Process Indirect Electrostatic Photographic Method

**Type** Desktop

 Original Scanning Method
 Contact Image Sensor (CIS)

 Resolution
 2400 x 600 dpi (with Smoothing)

Gradation 256 Steps

Original Platen Type Fixed Hard Platen, 50-Sheet RADF (14-28 lb)

Available Original Size ST-R to LD
Available Paper Size Drawer: LT Only

Stack Feed Bypass: ST-R, LT, LD, Envelope

Paper Supply Standard: Drawer (250 Sheets x 1) Stack Feed Bypass (50 Sheets)

Available Paper Weight Drawer: 17-20 lb

Stack Feed Bypass: 14-120 lb Index Auto Duplexing Unit: 17-20 lb

Paper Exit Face Down/Inner Tray

Warm-up Time Approx. 18 Seconds (Scanner Function Available

During Warm-Up)

Counter Electronic Counter (Indication by LCD Display)

Memory512 MBDepartment Codes100

Power Supply 115 Volts, 12 Amps
Power Consumption Maximum: 1.5kW
TEC Value 1.4kWh/week

**Dimensions** Approx. 15.3" x 21.25" x 20" (W x D x H)

Weight Approx. 58.3/62.7 lb

**Special Features** Energy Saver, Auto Sleep Mode, Department Code

Max Duty Cycle 64K Copies

**Certifications** Energy Star V3.0, EPEAT (GOLD) & WEE (Argentina

Model) + RoHS Compliant

Worldwide Safety Stds. UL, GS, CE, CDRH, SASO, IRAM, EAC, CCC

**Black Toner Yield** 17.5K Impressions @ 5%

## **Copy Specifications**

Copying Speed 28 PPM

Original Scan Speed 25 SPM (by Using RADF)
Scan Resolution 600 x 600 dpi (for Copying)
First Copy Time Less Than 6.5 Seconds

Original/Copy Size ST-R to LD

Original Mode Photo, Text/Photo, Text, Background Erase

 Image Density Control
 Automatic/Manual (11 Steps)

 Reproduction Ratio
 Zoom: 25% to 400% in 1% Increments

 Multiple Copying
 Up to 999 Copies (Ten Key Input)

Special Features Department Codes (100) Interrupt, APS/AMS,
Auto Job Start, Automatic Sort Mode, ID Card Copy,

One Touch Keys (2)

## **Print Specifications**

PDI

Printing Speed 28 PPM

**Printing Resolution** 2400 x 600 dpi (with Smoothing) **Interface** Standard: 10/100 Base-T, USB 2.0

Optional: 802.11 b/g/n PCL 6 Emulation

**USB Direct Printing** JPEG, TIFF, PDF (Only PDF created by MFP

can be printed)

**Support OS** Windows 7, 8, 8.1, 10, 2008R2, 2012, 2012 R2, (WHQL),

CUPS PCL Unix, Linux 5.10.x, 6.5.x

### Scan Specifications

Connection Type Standard: 10/100 Base-T

Optional: 802.11 b/g/n

**Scanning Resolution** 100/150/200/300/400/600 dpi

Scanning Speed 25 SPM (BW) at 600 dpi, 22 SPM (Color) @ 200 dpi,

13 SPM @ 300 dpi

Scan Agent Scan to File, SMB, FTP, Scan to Email, Scan to USB, TWAIN

IOS & Android Support Via e-BRIDGE Print & Capture App

(Free on iStore or Play)

# **Paper Handling**

#### **Reversing Automatic Document Feeder (RADF)**

Stack Capacity50 SheetsOriginal SettingFace UpOriginal Paper SizeST-R to LDOriginal Paper Weight14-28 lb

FAX Specifications (e-STUDIO2822AF Only)

Compatibility Super G3, G3
Image Format on PSTN JBIG, MMR, MR, MH
Document Size ST-R-I D

 Document Size
 ST-R-LD

 Modem Speed
 33.6 kbps to 2.4 kbps (Automatic Fallback)

Transmission Speed Approx. 3 Seconds
Communication Protocols ITU-T T.30

Memory Transmission Max 256 Jobs, 220 Destinations/Job, 384 Pages/File

Options

 Cabinet
 STAND2505

 Wireless LAN Module
 GN1160

 Damp Heater (for Drum)
 MF2505U

 Harness for Coin Controller
 GQ1131











\*Fax available with AF model only

Designs and specifications subject to change without notice. Specifications may vary by conditions of use and/or environmental usage. For best results and reliable performance, always use supplies manufactured or designated by Toshiba. Not all options and accessories may be available at the time of product launch. Please contact a local Authorized Toshiba Dealership for availability. Toner yields are estimates based on 5% coverage, letter-size page. Driver and connectivity feature support varies by client/network operating system. Product names may be trademarks of their respective companies. AirPrint® and the AirPrint® logo are trademarks of Apple Inc. This is a Class 1 laser product complying with IEC60825-1. All company and/or product names are trademarks and/or registered trademarks of their respective manufacturers in their markets and/or countries.

Corporate Office

**East Coast** 

West Coast

Midwest

South

25530 Commercentre Drive, Lake Forest, CA 92630 Tel: 949-462-6000 959 Route 46 East, 5th Floor, Parsippany, NJ 07054

Tel: 973-316-2700

8770 W. Bryn Mawr Ave., Suite 700, Chicago, IL 60631

Tel: 773-380-6000

2037 Bakers Mill Rd., Dacula, GA 30019

Tel: 678-546-9385

25530 Commercentre Drive, Lake Forest, CA 92630

Tel: 949-462-6000
Web Site www.business.toshiba.com