

TOSHIBA

e-STUDIO5528A/6528A

- High-Speed – Up to 55 & 65 PPM
- High-Volume
- Advanced Security Features
- Solutions Ready
- Environmentally Friendly



MAIN SPECIFICATIONS

| | |
|---------------------------------|--|
| Copy Process | Indirect Electrostatic Photographic/OPC/Laser Printing/Heat Roller Fusing |
| Display | 10.1" Color WSVGA Touch Screen Tilting Display |
| Copy Speed | 55/65 PPM (LT) |
| Warm-Up Time | Monochrome: Less Than 4.3/4.3 Seconds From Powering on: Approx. 26 Seconds From Sleep & Low Power: Less Than 20 Seconds |
| Copy Resolution | 600 x 600 dpi |
| Stack Feed Bypass | 3.9" x 5.8" to 12.5" x 18", 12" x 47" Banner, Envelope |
| Multiple Copying | Up to 999 Copies |
| Paper Capacity | Standard 1,200 Sheets/Max. 5,200 Sheets |
| Original Feed | 300-Sheet DSD/ or DSD/ with Double Feed Detection or 100-Sheet RADF |
| Scan Speed & Weights | DSD/ Scan: 70IPM, (Monochrome or Color), Simplex or Duplex: 9.3-110lb Bond RADF Scan: 50IPM, (Monochrome or Color), Simplex: 9.3-41.8lb Bond Duplex: 13.3-41.8lb Bond LD/A3 Drawer 1: 550 Sheets-ST-R to LD Drawer 2: 550 Sheets-ST-R to 12.5" x 18" Stack Feed Bypass: 100 Sheets-3.9" x 5.8" to 12.5" x 18", 12" x 47" Banner Opt. 550-Sheet Paper Feed Pedestal-ST-R to 12.5" x 18" Opt. 550-Sheet Drawer for PFP-ST-R to 12.5" x 18" Opt. Envelope Cassette for PFP-Approx. 60 Envelopes/550 Sheets-ST-R to LG Opt. 2,000-Sheet Tandem LCF (Pedestal Type)-LT Only Opt. 2,000-Sheet External LCF-LT Only Standard: 550 Sheets x 2-16lb Bond-110lb Cover Stack Feed Bypass: 100 Sheets-14lb Bond-110lb Cover Banner up to 90lb Index Opt. 550-Sheet Paper Feed Pedestal-16lb Bond-140lb Index Opt. 550 Sheets Drawer for PFP-16lb Bond-110lb Cover Opt. Envelope Cassette for PFP-16lb Bond-110lb Cover Opt. 2,000-Sheet Tandem LCF (Pedestal Type)-16lb Bond-110lb Cover Opt. 2,000-Sheet External LCF-LT-16lb Bond-110lb Cover Standard Automatic Duplex Unit (16lb Bond-140lb Index) |
| Max. Original Size | 25% to 400% |
| Paper Feed Sizes | Max. 223K/243K Month Approx.159lb 26" (W) x 25.2" (D) x 41.2" (H) 39.8K @ 5% 120 Volts, 50/60 Hz, 12 Amps Maximum 1.8kW (120V) NEMA 5-15 6GB 128GB Solid State Drive (SSD) |
| Paper Weights | |
| Duplex | |
| Reproduction Ratio | |
| Max Duty Cycle | |
| Weight | |
| Approx. Dimensions | |
| Toner Yield | |
| Power Source | |
| Power Consumption | |
| Plug Type | |
| Memory | |
| Hard Disk Drive | |

e-BRIDGE NEXT PRINT SPECIFICATIONS

| | |
|-------------------------------|--|
| PDL | PCL5e, PCL5c, PCL6 (PCL XL), PS3, PDF, XPS, JPEG |
| Print Resolution | 600 x 600 dpi (5 bit), 1,200 x 1,200 dpi (2 bit) or 3,600 (Equivalence) x 1,200 dpi (BW/with Smoothing) (PS3 Only) |
| Operating Systems | Windows® 8.1, 10, 11, Windows Server® 2012/R2, Windows Server® 2016/19/22, Macintosh® (macOS X 10.10-15, 12), Unix®, Linux® |
| Network Protocols | TCP/IP (IPv4, IPv6), NetBIOS over TCP/IP, IPX/SPX® for Novell® Environments, EtherTalk for Macintosh Environments |
| Printing Protocols | SMB V1-3, LPR/LPD, IPP V1.2 w/Authentication (TLS 1.2/1.3), AppleTalk® PAP or EtherTalk, Port 9100 (Bi-Directional), NetWare P-SERVER LPD w/iPrint, Bluetooth (HCRP/BIP/OPP/FTP), WS Print, FTP |
| Print Drivers | Windows® 8.1 (32-bit, 64-bit), Windows Server® 2012/R2 (64-bit), Windows Server® 2016/19/22, Windows® 10, 11 (64-bit), macOS X 10.12-15, 11, 12 |
| Interface | RJ-45 Ethernet (10/100/1000 Base-T), USB 2.0 (High-Speed) Optional IEEE802.11b/g/n, Wireless LAN, Optional Bluetooth |
| Wireless Device | AirPrint®, Mopria®, e-BRIDGE Print & Capture Application on iOS and Android (Available via Apple® App Store or Google Play) |
| Device Management | TopAccess |
| Account Control | Up to 10,000 Users or 1,000 Departments Supports User Authentication (on Device), Login Name/Password (via Windows® Domain) or Login Name/Password (via LDAP Server) for Copy, Print, Scan, Fax, List, and User Function |
| Accessibility Features | Tilt Front Panel, Job Programs, Universal Grip for Paper Trays, Disable Screen Timeout, Audible Beeps, Optional Voice Assist |



Security Features

User Authentication, Trusted Platform Module, On-Board Data Scramble Function, SCEP, Disable, e-Filing, Disable Copy, Disk Overwrite, IP Address Filtering (10 Sets), MAC Address Filtering (10 Sets), Network Service Control, Network Port Control, SMB Packet Signing, SSL/TLS (HTTP, IPP, LDAP, SMTP, POP, FTP, DPWS, SYSLOG), IPsec (IKEv1, IKEv2), Security Mode Change, CC Certified (ISO/IEC15408)* with HCD-PP v1.0, IEEE802.1X (Wired/Wireless), Digital Signature for Client Utilities, Password Policy, Password Lock, Password Expiration, Self Testing, Job Access Control, Log Access Control for Job Log, Security Stamp, Role Based Access Control, Secure PDF, Digital Signature for Firmware Update, Integrity Check Function, Image Log, Card Authentication, Biometric Authentication *Conformance with HCD-PPv1.0 in High Security Mode ENERGY STAR® (V3.1), EPEAT Gold, Californian Proposition 65 WHQL (Windows® 8, 8.1, 10, 11, 2012, 2012 R2, 2016/19/22), Novell®, Citrix®, SAP, AirPrint® and Mopria®

Environmental Standards Certifications

SCAN SPECIFICATIONS

| | |
|--------------------------|---|
| Scan Speed | DSD/ Scan: Up to 240 IPM Duplex, 120 IPM Simplex (Monochrome or Color) RADF Scan: Up to 73 IPM (Monochrome or Color) Standard: Full Color, Auto Color, Monochrome, Grayscale DOC/XLS/PPT/PDF |
| Scan Modes | 600 dpi, 400 dpi, 300 dpi, 200 dpi, 150 dpi, 100 dpi |
| OCR | Monochrome: TIFF-Multi/Single Page, PDF-Multi/Single Page, Searchable PDF, XPS-Multi/Single Page, DOCX, XLSX, PPTX |
| Scan Resolution | Color/Grayscale: JPEG, TIFF-Multi/Single Page, PDF-Multi/Single Page, Slim PDF, Searchable PDF, XPS-Multi/Single Page, DOCX, XLSX, PPTX |
| File Formats | Color/Grayscale: JPEG (High, Middle, Low) |
| Image Compression | |

FACSIMILE SPECIFICATIONS

| | |
|----------------------------|---|
| Compatibility | Super G3 |
| Data Compression | MH/MR/MMR/JBIG |
| Transmission Speed | Approx. 3 Seconds Per Page |
| Fax Modem Speed | Up to 33.6 Kbps |
| Memory Transmission | 100 Jobs (with HDD), 2,000 Destinations Max. 400 Destinations/Job |
| Scan Speed | 0.7 Seconds Per Page, Maximum 73 IPM |

e-FILING SPECIFICATIONS

| | |
|--------------------------|---|
| Operation Method | Color Touch Screen Control Panel or Client PC |
| Number of Boxes | 1 Public Box, 200 Private User Boxes |
| Capacity of Boxes | 100 Folders Per Box, 400 Documents Per Folder/Box, 200 Pages Per Document |

ACCESSORIES (OPTIONS)

| | | | |
|---|------------|------------------------------|------------|
| Platen & Document Feeder Options | | Unicode Font Enabler | GS1007NODE |
| DSD/ | MR4010 | Multi-Station Print Enabler | |
| DSD/ with Double Feed Detection | MR4020 | Per Seat License | GS1090NODE |
| RADF | MR3033 | e-BRIDGE Plus for OneDrive | |
| Platen Cover | KA5005PC | for Business V3.0 | GB2300NODE |
| Additional Paper Options | | e-BRIDGE Plus for SharePoint | |
| Paper Feed Pedestal | KD1072 | Online V3.0 | GB2310NODE |
| Drawer Module | MY1052 | e-BRIDGE Plus for Exchange | |
| Envelope Cassette Option | MY1053 | Online V3.0 | GB2320NODE |
| Large Capacity Feeder | KD1073LT | e-BRIDGE Plus for Gmail | GB2380NODE |
| External Large Capacity Feeder | MP2002L | e-BRIDGE Plus for Google | |
| Finishing Options | | Workspace | GB2390NODE |
| 65-Sheet Staple Finisher | MJ1113 | Security SSD (512GB) | GE1280 |
| 65-Sheet Saddle-Stitch Finisher | MJ1114 | FIPS HDD (320GB) | GE1260 |
| Hole Punch for MJ1113/MJ1114 | MJ6107N | e-BRIDGE Plus Voice Guidance | GB2540NODE |
| Bridge Kit | KN5005 | e-BRIDGE Global Print | GB2550NODE |
| Job Separator | MJ5015 | Miscellaneous Options | |
| Connectivity/Security Options | | Card Reader Holder | GR1320 |
| FAX Unit/2 nd Line for FAX Unit | GD1370N | Accessory Tray | GR1330 |
| Wireless LAN/Bluetooth | GN4030A3 | Panel 10-Key Option | GR1340 |
| Fax Over IP License Key | GS1100NODE | Stand | STAND5015 |
| Bluetooth Keyboard | GR9001 | Work Tray | KK5005 |
| 2 nd NIC Holder | GR1430 | Manual Pocket | KK5008 |
| USB Hub | GR1420 | Harness for Coin Controller | GQ1280 |
| Meta Scan Enabler | GS1010NODE | Accessible Arm | KK2560 |
| IPSec Enabler | GP1080NODE | | |

Corporate Office

25530 Commercentre Drive, Lake Forest, CA 92630
Tel: 949-462-6000

East Coast

959 Route 46 East, 5th Floor, Parsippany, NJ 07054
Tel: 973-316-2700

Midwest

8770 W. Bryn Mawr Ave., Suite 700, Chicago, IL 60631
Tel: 773-380-6000

South

2037 Bakers Mill Rd., Dacula, GA 30019
Tel: 678-546-9385

West Coast

25530 Commercentre Drive, Lake Forest, CA 92630
Tel: 949-462-6000

Website

www.business.toshiba.com

Designs and specifications subject to change without notice. Specifications may vary by conditions of use and/or environmental usage. For best results and reliable performance, always use supplies manufactured or designated by Toshiba. Not all options and accessories may be available at the time of product launch. Please contact a local Authorized Toshiba Dealership for availability. Toner yields are estimates based on 5% coverage, letter-size page. Driver and connectivity feature support varies by client/network operating system. Product names may be trademarks of their respective companies. AirPrint® and the AirPrint® logo are trademarks of Apple Inc. This is a Class 1 laser product complying with IEC60825-1. All company and/or product names are trademarks and/or registered trademarks of their respective manufacturers in their markets and/or countries.